

QPOS Trio

MINI POS

**Efficient Payments, Seamless Integration.
Portable, Durable, and Adaptable.**

PCI PTS 6.x with SRED

Linux OS with ARM Cortex-A7 Dual Core CPU

2.4-inch color display with touchscreen

3.7V/4000mAh battery

50mm/s thermal printer

4G, WiFi connectivity options



Wi-Fi



4G Network



GPS



Printer



PIN pad

Specification

QPOS Trio

OS	Linux
Processor	ARM Cortex-A7 Dual Core 1.0 GHz
Memory	128MB RAM, 128M Flash
Display	2.4" 320 x 240 TFT Display Capacitive Touchscreen
Communications	4G/2G WiFi: 802.11 b/g/n, 2.4GHz
Audio	Built-in buzzer
Printer	Thermal printer Paper Roll Width: 58mm Paper Roll Diameter: 40mm
Magnetic Card Reader	Triple track, conforming to ISO 7810/7811/7813, Bi-directional swiping
EMV Card Reader	EMV L1/L2, conforming to ISO 7816, compliant Class A, B, C
Contactless Card Reader	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare
Keys / Buttons	16 Keys: 0~9 5 Function Keys 1 Power ON / OFF
Certifications	PCI PTS 6.x with SRED EMV L1&L2, Contactless L1 Visa Paywave, MasterCard Paypass, PURE Amex Expresspay, Discover D-PAS PCI PIN Security, MasterCard TQM CE, FCC, RoHS
Adapter/Power Supply	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
Battery	3.7V/4000mAh
Peripheral Ports	Type-C USB 1 Mini SIM + 1 Mini SAM
Environmental Conditions	Operating temperature: 0°C~45°C Storage temperature: -20°C~60°C Relative humidity: 5%~95% (Non-condensing)
Dimensions	153mm x 78mm x 61.6mm, 348g(Including Battery)
Standard Accessories	1 Power adapter, 1 USB cable